



Stock # **TRL19855**

Last 5 **32272**

Load King Model: Signature Series 554 SS
(Signature Series - 55 Ton Hydraulic Detachable Gooseneck Quad Axle)

General		Subframe	
110,000# capacity in 12' load concentration with stinger		Quad Axle Straight 4	0
100,000 / 80,000 psi yield steel mainbeams		Lift Axle Options	
Est. weight (lbs):	27,700 not incl. attachments, +/- 5%	Air lift 3rd & 4th axle w/manual raise & lower valve, +3 / -3 off leveling valve	
Overall length:	57' - 6 1/2" not incl attachments	Axle spacing: 54.5"	0
102" wide (deck and axles)	0	Sixteen 255/70R22.5 H radials	0
Hendrickson Air-Ride		Sixteen 8.25 x 22.5 hub piloted steel disc wheels	0
Four 27,500 lb axles- 5" x 3/4" wall		16 1/2 in. x 7 in. drum brakes, no ABS	0
		Spring brakes on axle 2	0
		Three tail light package with strobes	0
		Boom trough, open to tailgate	0
		Covered wheel wells - (2) piece flat bolt on style	2,180
		Wide Load sign pockets (no sign)	0
		Lowered crossmembers in subframe	
		Other options: none	0
		5 Pair Flat D-Rings mounted on Upper Flange	
Gooseneck		Other	
Hydraulic non-ground bearing Scraper neck		DOT rubber-mounted LED lights & sealed harness	
12'-9" gooseneck with 110" & 86" swing	0	Safety mid ship turn mounted on center pull out	
51" 5th wheel height - adjustable with 5 position ratchet		Black rubber Load King mud flaps, conspicuity tape	
High clearance frame recess with hydraulic frame lift support arm		Other general options: none	
Air-activated, self-locking pin on gooseneck, positive Safety lock		Load King Black 2-part polyurethane	
13 HP Honda mounted over Kingpin	275		
Other Gooseneck options: none	0		
Deck		Attachments included:	
4 full depth 12 in. cambered deck beams		Connections & reinforcing for future 4th axle flip	
26 ft. deck length - flat	0	Addl. Flip axle options: none added	
13 Pair chain slots in outer flanges			
Alternating 10" & 4" crossmembers on 12 in. centers			
18 in. loaded deck height with 6" loaded ground clearance	1045		
2" Apitong (nominal) in track area bolted at all board ends			
Open in center of deck	0		
Outriggers: 13 Pair swing out - removable			
Wide Load Package- gussets behind each outrigger			
Boxed Front Approach & Upper Flange Reinforcement			
Bend D-rings - 6 per side, mounted to Reinforcement			
Recessed last 8 ft. of deck with pierced steel plate			
Pierced Steel tool box - 60" at front	0		
30" front flip ramps - bridge style spring assisted	0		
32 degree radius to subframe - ramp to subframe			
		Special Options	
		Load King - Elk Point, SD	
			Est Wt