

Chassis VIN: 1FVACXDT9FHGL0187

Chassis Milage: 44,280

Aerial Serial Number: 2141152695

# 2014 Terex TC55 2015 Freightliner M2106 4x2

# **CHASSIS SPECS**

#### Engine

Cummins ISB 250hp 660lb ft (2) 12V Batteries 18.7 CFM Air Compressor w/ Internal Safety Valve 115V Block Heater

#### Transmission

Allison 3500RDS w/ PTO Provision Electronic Cruise Control

# Front Axle

Detroit DA-F-13.3-3 FAWR: 13,300 lbs Tires: 11R22.5 Aluminum Wheels Suspension:

Taperleaf Springs 13,300 lbs Front Shock Absorbers

Maintenance Free Rubber Bushings

#### Rear Axles

Meritor MS-21-14X Ratio 6.43 RAWR: 21,000 lbs R-Series Tires: 11R22.5 Steel Wheels Suspension: Variable Multi-Leaf 23,000 lbs.

w/ Spring Helper

## **Fuel Tanks**

50 Gal. Aluminum-LH 6 Gallon DEF Tank

# Frame & Bumper

Battery Box Frame Mounted 189" Wheelbase 7/16x3-9/16x11-1/8" Steel Frame 3-Piece 14" Painted Steel Bumper Front Tow Hooks **Brake & Trailer System** Air Brakes

WABCO 4S/4M ABS Brake Line Air Dryer w/ Heater Steel Air Brake Reservoirs Air Connections EOF w/ Glad Hands SAE J560 7-Way Primary Receptacle Trailer Hand Brake Control Valve

#### **Cab Features:**

106" BBC Flat Roof Cab Conventional, Aluminum Fiberglass Hood Single Electric Horn Single Under Cab Air Horn (5) Amber Marker Lights Dual West Coast Molded-In Color Mirrors Opal Gray Vinyl Interior Heater, Defroster, A.C. Full Width Bench Seat (1) 12V Power Supply In-Dash Fixed Steering Column Driver Instrumentation Display AM/FM/WB Radio -w/Front Aux. Input





Photos Are Of A Similar Truck - For Reference Only





# 888-684-8146 www.customtruck.com

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

# DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions. Pictures are representative and may not be identical.

# **EQUIPMENT SPECS**

### **Aerial Specifications**

Insulated, Non-Overcenter Aerial Device

Category B Machine In Accordance w/ ANSI/SIA A92.2-2009

Working Height: 60 ft.; Side Reach: 42.8 ft.

Closed-Center, Parallel Circuit Hydraulic System, Operating Pressure: 2500 PSI

Hydraulic Hoses Equipped w/ Permanent Type Hose Fittings

Platform Leveling Control at Top Controls; Load Chart Stating Actual Lifting Capacity

All Aerial Metallic Components - Prime Painted

Fiberglass Upper Boom/Lower Boom Insert: White Platforms & Covers

Two Complete Manuals Providing Operation/Maintenance Procedures

Continuous Unrestricted Rotation; Pedestal Designed w/ Access Holes

Individual Control Levers at Turntable, Upper/Lower Control Selector

Provides Override of Platform Controls /Winch Control at Lower Controls

Self-Locking Worm Gear Rotation Drive w/ Bi-Directional Motor

Boom w/ Standard Upper Boom Rest w/ Cam Type Tie Down Strap

Lower Boom: 116 Degree Articulation Filament Wound Hi-Strength Fiberglass Insert

Lower Boom Insert

Boom Tip w/ Hydraulic Platform Rotator: Upper Controls Single Stick Controller

Platform Rotator Offering 90 Degrees of Hydraulic Rotation; Platform Capacity: 700 lbs.

Hydraulic Platform Tilt at Platform & Lower Controls

Engine Start/Stop at Platform & Lower Controls

Dual Hydraulic Tool Outlets at Platform w/ Flow Control; Includes Bleeder Spool

Accommodates 2 Closed Center Hydraulic Tools/Includes Port Relief/Quick Disconnect Couplers

Side Mounted Fiberglass Platform 24" x 48" x 42" (Curbside) w/ 2 Outside

Access Steps w/ Slip-Resistant Surface

2 Safety Harnesses/Lanyards & Platform Rest Saddle w/ Padded Rest for Travel

Insulated Platform Liner for 24" x 48" x 42" Platform (50 KV AC)

Waterproof Vinyl Platform and Control Cover for Platform

Hydraulic Extendable Underslung Jib & Winch - 1,500 lbs Capacity

Hydraulic Oil Reservoir Includes 100 Mesh Filter, 10u Return Filter w/ Shut Off Valve

(1) Auxiliary Let Down for Use w/ Closed Center Hydraulics

Subframe Constructed w/ an Open Center; 1 Tie Down Kit Included

(2) Heavy Duty A-Frame Outriggers w/ Swivel Type Stabilizer Pads

Controls for 2 Sets of Outriggers w/ Auxiliary Tool Outlets

Rubber Wheel Chocks

Outrigger Pads

#### Note:

These trucks/equipment are off-lease rental units that have been maintained by custom truck one source. Qualifies for a 2 year/50,000 mile warranty for the truck and rear apparatus. Ask your sales representative for details

> Call For Price Plus Applicable Taxes And Transportation Ex Works: Fontana, CA

OUOTE NUMBER: JP12.1-D 20

**EXPIRATION DATE:**