Stock # ***TRL19354***
Last 5 ***32072***

Load King Model: *Signature Series 503/605 SS SFF*

(Signature Series - 60 Ton Hydraulic Detachable Gooseneck Reinforced for a Stinger, 2 Flip Axles and Single or Tandem Axle Jeep)

General

120,000# capacity in 12' load concentration with stinger

100,000 / 80,000 psi yield steel mainbeams

Est. weight (lbs): 24,820 not incl. attachments, +/- 5%

Overall length: 52' - 11" not incl attachments

9' wide (deck and axles)		1,380

Hendrickson Air-Ride

Gooseneck

Hydraulic non-ground bearing Scraper neck

Work lights on gooseneck

12'-9" 110" & 86" swing w/conn for 36" flip box, 146" swing		0

51" 5th wheel height - adjustable with 5 position ratchet

High clearance frame recess with hydraulic frame lift support arm

Air-activated, self-locking pin on gooseneck, positive Safety lock

Hydraulic power from tractor source		0
Other Gooseneck options: none		0

Deck

4 full depth 16 in. cambered deck beams

25 ft. deck length - flat		-275

13 Pair chain slots in outer flanges

Alternating 10" & 4" crossmembers on 12 in. centers

24 in. loaded deck height with 8" loaded ground clearance		0

2" Apitong (nominal) in track area bolted at all board ends

Open in center of deck		0

Outriggers: 13 Pair swing out - removable

Wide Load Package- gussets behind each outrigger

Boxed Front Approach & Upper Flange Reinforcement

Bent D-rings - 6 per side, mounted to Reinforcement

Recessed last 8 ft. of deck with pierced steel plate

Pierced Steel tool box - 60" at front	$0	0

30" front flip ramps - bridge style ***spring assisted***

32 degree radius to subframe - ramp to subframe

Subframe

Frame reinforcing & connections for future stinger & 2 Flip axle (5 axles total)

Air lift 3rd axle w/manual raise & lower valve, +3 / -3 off leveling valve

Three 27,500 lb axles- 5" x 3/4" wall

Axle spacing: 60"		150
Twelve 275/70R22.5 H radials		0
Twelve 8.25 x 22.5 hub piloted steel disc wheels		0
16½ in. x 7 in. drum brakes, no ABS		0
Spring brakes on axle 2		0
Three tail light package with strobes		0
Boom trough, open to tailgate		0
Flush mount bolsters with open wheel wells		0
Wide Load sign pockets (no sign)		0

Lowered crossmembers in subframe

Other options: none		0

4 Pair Flat D-Rings mounted on Upper Flange

Other

DOT rubber-mounted LED lights & sealed harness

Mid ship turn signal w/ dual intensity rear marker lights

Black rubber Load King mud flaps, conspicuity tape

Other general options: none		0
Load King Black 2-part polyurethane		0

Attachments included:

Connections & reinforcing for future 14' 1" stinger Addl spreader bar options: none added		0
Connections & reinforcing for future 4th & 5th axle flip Addl. Flip axle options: none added		0

Special Options	**Price**	**Est Wt**
Load King - Elk Point, SD		