



Chassis VIN: 3ALACXY9FDGG4127  
Chassis Mileage: 43,168  
Aerial Serial Number: 2140752913

# 2014 Terex TC55 2015 Freightliner M2106 4x2

## CHASSIS SPECS

### Engine

Cummins ISL 300hp 860lb ft  
(2)12V Batteries  
18.7 CFM Air Compressor  
w/ Internal Safety Valve  
115V Block Heater

### Transmission

Allison 3500RDS  
w/ PTO Provision  
(1) Dash Mounted PTO Switch  
w/ Indicator Lamp  
Electronic Cruise Control

### Front Axle

Detroit DA-F-12.0-3  
FAWR: 12,000 lbs  
Tires: 11R22.5  
Aluminum Wheels  
Suspension:  
Dual Taperleaf Springs 12,000 lbs  
Front Shock Absorbers  
Maintenance Free Rubber Bushings

### Rear Axles

DA-RS-21.0-4 Rear Axle  
Ratio 5.22  
RAWR: 21,000 lbs R-Series  
Tires: 11R22.5  
Steel Wheels  
Suspension:  
Variable Multi-Leaf 23,000 lbs.  
w/ Spring Helper

### Fuel Tanks

50 Gal. Aluminum-LH  
6 Gallon DEF Tank

### Frame & Bumper

Battery Box Frame Mounted  
186" Wheelbase  
7/16x3-9/16x11-1/8" Steel Frame  
3-Piece 14" Painted Steel Bumper  
Front Tow Hooks

### Brake & Trailer System

Air Brakes  
WABCO 4S/4M ABS  
Brake Line Air Dryer w/ Heater  
Steel Air Brake Reservoirs  
Air Connections EOF w/ Glad Hands  
SAE J560 7-Way Primary Receptacle  
Trailer Hand Brake Control Valve

### Cab Features:

106" BBC Flat Roof Cab  
Conventional, Aluminum  
Fiberglass Hood  
Dual Electric Horn  
Single Under Cab Air Horn  
(5) Amber Marker Lights  
Dual West Coast Bright Finish Mirrors  
Opal Gray Vinyl Interior  
Heater, Defroster, A.C.  
Basic High Back Air Suspension Driver Seat  
Basic High Back Non-Suspension Pass Seat  
(1) 12V Power Supply In-Dash  
Adjustable Tilt/Tele. Steering Column  
97 DB Backup Alarm  
Driver Instrumentation Display  
AM/FM/WB World Tuner Radio  
-w/ Front Aux. Input  
White Paint



## EQUIPMENT SPECS

### Aerial Specifications

Insulated, Non-Overcenter Aerial Device  
Category B Machine In Accordance w/ ANSI/SIA A92.2-2009  
Working Height: 60 ft.; Side Reach: 42.8 ft.  
Closed-Center, Parallel Circuit Hydraulic System, Operating Pressure: 2500 PSI  
Hydraulic Hoses Equipped w/ Permanent Type Hose Fittings  
Platform Leveling Control at Top Controls; Load Chart Stating Actual Lifting Capacity  
All Aerial Metallic Components - Prime Painted  
Fiberglass Upper Boom/Lower Boom Insert: White Platforms & Covers  
Two Complete Manuals Providing Operation/Maintenance Procedures  
Continuous Unrestricted Rotation; Pedestal Designed w/ Access Holes  
Individual Control Levers at Turntable, Upper/Lower Control Selector  
Provides Override of Platform Controls /Winch Control at Lower Controls  
Self-Locking Worm Gear Rotation Drive w/ Bi-Directional Motor  
Boom w/ Standard Upper Boom Rest w/ Cam Type Tie Down Strap  
Lower Boom: 116 Degree Articulation Filament Wound Hi-Strength Fiberglass Insert  
Lower Boom Insert  
Boom Tip w/ Hydraulic Platform Rotator: Upper Controls Single Stick Controller  
Platform Rotator Offering 90 Degrees of Hydraulic Rotation; Platform Capacity: 700 lbs.  
Hydraulic Platform Tilt at Platform & Lower Controls  
Engine Start/Stop at Platform & Lower Controls  
Dual Hydraulic Tool Outlets at Platform w/ Flow Control; Includes Bleeder Spool  
Accommodates 2 Closed Center Hydraulic Tools/Includes Port Relief/Quick Disconnect Couplers  
Side Mounted Fiberglass Platform 24" x 48" x 42" (Curbside) w/ 2 Outside  
Access Steps w/ Slip-Resistant Surface  
2 Safety Harnesses/Lanyards & Platform Rest Saddle w/ Padded Rest for Travel  
Insulated Platform Liner for 24" x 48" x 42" Platform (50 KV AC)  
Waterproof Vinyl Platform and Control Cover for Platform  
Hydraulic Extendable Underslung Jib & Winch - 1,500 lbs Capacity  
Hydraulic Oil Reservoir Includes 100 Mesh Filter, 10u Return Filter w/ Shut Off Valve  
(1) Auxiliary Let Down for Use w/ Closed Center Hydraulics  
Subframe Constructed w/ an Open Center ; 1 Tie Down Kit Included  
(2) Heavy Duty A-Frame Outriggers w/ Swivel Type Stabilizer Pads  
Controls for 2 Sets of Outriggers w/ Auxiliary Tool Outlets  
Rubber Wheel Chocks  
Outrigger Pads

### Note:

These trucks/equipment are off-lease rental units that have been maintained by custom truck one source. Qualifies for a 2 year/50,000 mile warranty for the truck and rear apparatus.  
Ask your sales representative for details

888-684-8146 [www.customtruck.com](http://www.customtruck.com)

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING  
SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions.  
Pictures are representative and may not be identical.

Call For Price  
Plus Applicable Taxes And Transportation  
Ex Works: Cabot, AR

QUOTE NUMBER: JP7.1-D\_20

EXPIRATION DATE: