



2015 Freightliner M2106 AWD

Terex HRX55 Aerial Device

CHASSIS SPECS

Unit Information

Vin # 3ALDCXDT5FDGB6592

Dash: 62,678

AWD Single Axle

Pintle Hitch

Engine

Cummins ISB 6.7 250 HP
(2) Alliance 12V Batteries
18.7 CFM Air Compressor Turbocharged
w/ Internal Safety Valve
115V Block Heater

Transmission

Allison 3500 RDS Automatic
w/ PTO Provision
(1) Dash Mounted PTO Switch
w/ Indicator Lamp
Electronic Cruise Control

Front Axle

FAWR: 14,000 lbs
Tires: 11R22.5
Steel Wheels
Suspension:
Taperleaf 14,600 lbs
Front Shock Absorbers
Maintenance Free Rubber Bushings

Rear Axles

RAWR: 21,000 lbs
Tires: 11R22.5
Steel Wheels
Differential Lock
Suspension:
23,000 lbs. Multi-Leaf with Helpers

Fuel Tanks

50 Gal. Aluminum-LH
6 Gallon DEF Tank

Frame & Bumper

Battery Box Frame Mounted
191" Wheelbase
7/16x3-9/16x11-1/8" Steel Frame
Front Tow Hooks

Brake & Trailer System

Air Brakes
Steel Air Tanks

Cab Features:

106" BBC Flat Roof Cab
Conventional, Aluminum
Fiberglass Hood
Single 14" Round Hadley Air Horn
Dual Electric Horn
(5) Amber Marker Lights
Dual West Coast Mirrors
Opal Gray Vinyl Interior
Heater, Defroster, A.C.
Driver's Seat: High Back Air Suspension
Passenger's Seat: High Back Non Air
Suspension
(1) 12V Power Supply In-Dash
97 DB Backup Alarm
Driver & Center Instrumentation Displays
AM/FM Radio W/ Bluetooth, USB PORT,
and Aux. Inputs
White Paint



EQUIPMENT SPECS

General Specifications

Insulated Overcenter Aerial Device - Working Height 60.3'
Platform Leveling Control @ Top Controls, Hydraulic Platform Tilt @ Upper And Lower Controls
Self-Locking Worm Gear Rotation Drive
Full Pressure 3000 PSI Open Center Hydraulic System
120 Degree Lower Boom Articulation To Ground Access W/ Standard Upper Boom Rest & Cam Type Tie
Down Strap
Filament Wound High Strength Fiberglass Lower Boom Insert For Insulation Gap
Filament Wound Tapered Fiberglass Upper Boom Providing A Clear Span Insulation Gap
Category C Machine In Accordance W/ ANSI/SIA A92.2-2009
Boom Tip W/ 105 Degree Hydraulic Platform Rotator
"Control-Plus" Upper Controls - Single Stick Controller
Hydraulic Platform Rotator Offers 105 Degrees Of Forward Rotation
Engine Stop/Start At Platform And Lower Controls
Engine Throttle Controls
Dual Hydraulic Tool Outlets @ Platform W/ (2) Flow Controls
Auxiliary 12V Power
24" X 48" X 42" Side Mount (Curbside) Platform W/ Access Step W/ Slip Resistant Surface
(2) Safety Harnesses W/ Lanyards
Padded Saddle Rest For Platform Support
Insulated Platform Liner Tested @ 50 KV AC
Vinyl Platform And Control Cover
700 Lbs Rated Platform Capacity
2000 Lb Hydraulic Articulating Jib And Winch
Infinite Positions Through 120 Degree Articulation Envelope
1' - 6' Of Extension And Four Pinning Positions
Full Drum Capacity Self-Locking Worm Gear Winch
1/2" x 75' Load Line W/ Swivel Hook And Latch And Load Chart
35 Gallon Hydraulic Reservoir
Continuous And Unrestricted Rotation
Tie-Down Kit
(2) Sets Of Heavy Duty X-Frame Outriggers & Controls w/ Swivel Type Stabilizer Pads

Warranty

Truck/Equipment is off-lease rental units that have been maintained by Custom Truck One Source. Qualifies for a 2 year/50,000 mile warranty for the truck and rear apparatus. Ask your sales representative for details.

888-684-8146 www.customtruck.com

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING
SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions.
Pictures are representative and may not be identical.

Call For Price

Ex Works: Houston, TX

QUOTE NUMBER: MTT2.15-D_20

EXPIRATION DATE: