

JAM² FACTORY



WHEEL SIZE	SIZE/CM	ARTICLE NO. EU
29"	S/41	628 514 120
29"	M/44	628 514 121
29"	L/47	628 514 122
29"	XL/50	628 514 123

- ▽ 7005 hydroformed aluminium, 3D forging, 140 mm F.O.L.D. kinematic, 148x12 mm through axle, internal cable routing, post mount 180 mm
- ↘ Fox 36 Performance, 110x15 mm QR, 150 mm travel
- mm Fox DPS, 210/55, hardware: shaft25,0x8 mm/body25,0x8 mm, custom tune
- 150/140 mm
- Shimano Steps E8000, 70 Nm, 250 W
- FOCUS T.E.C., 756 Wh, (378 Wh internal, 378 Wh optional external)
- FOCUS T.E.C., 4 Amp
- SHIMANO Steps E8000, colored LCD display, walk assist, bluetooth
- Sram EX1, 8-speed
- Sram EX1
- EX1 CS-XG 899 8S, 11-48T
- FC-E8000-34T
- BBB, aluminium, Di2, flatbar, 760 mm, rise: 0 mm, backsweep: 9°
- BBB, aluminium, Di2, 31,8 mm, 55 mm
- Acros AZX-212 AH, 1-1/8", tapered, HSZS 44/286-ZS56/40 W
- Trail Saddle
- Kind Shock E30i, 31,6 mm, internal
- Magura MT Trail Sport, 200 mm / 180 mm
- Race Face AEFECT R, 622-30, 148x12 mm / 110x15 mm
- Maxxis DHF 2.5/DHR 2.4
- Factory brown matt/Magicblack